

# ASTRA-A-SHADE CONCENTRATE

## product data sheet



### DESCRIPTION

ASTRA-A-SHADE Concentrate is designed specifically for use in Epoxy flooring system as a colouring agent..

The colorants are made with high quality pigments which have been chosen for their resistance to acids, alkali, solvents and for their light fastness. The very low binder/pigment ratios provide a powerful tinting strength. These colorants will not detract from the properties of the coating composition in which they are used.

### COLORS

ASTRA-A-SHADE is available in 15 standard colors. Please refer to the Standard Color Chart Custom colors are available upon request.

### TYPICAL USES

ASTRA-A-SHADE is designed for use in any Epoxy Systems as a colouring Agent.

### PACKAGING

ASTRA-A-SHADE Concentrate is available in 1,2,3,5 And 20 Kg pails.

### RECOMMENDED LEVELS OF USE

Coatings with ASTRA-A-SHADE Concentrates produce best results when they are applied with a paint roller or airless spray equipment. Brushes and wax type applicators can produce pigment floating and/or flooding.

### LIMITATIONS

1. Coatings tinted with ASTRA-A-SHADE are intended for application on horizontal surfaces such as floors.
2. A "wet edge" must be maintained during application. Division lines may be visible when a "wet edge" is not maintained.
3. Solvent borne coatings or Micron coatings will not provide color opacity in single coats. Multiple coats are needed to provide full hiding power.
4. Product is not designed for use in 100% solids epoxy systems, as pigment float will occur.

### MIXING INSTRUCTIONS AND APPLICATION

1. Pre-mix all ASTRA-A-SHADE to ensure color consistency.
2. Mix and Measure clear resin systems.
3. Mix 300gms- 400gms of ASTRA-A-SHADE for 6 Kgs of clear sealer or top coat. Mix well for 2 minutes.

Before using any ASTRA. product, be sure the Material Safety Data Sheet is read and understood.

### WARRANTIES

Seller warrants that its goods, as described on the face hereof, are free from any defects in material or workmanship. Seller makes no other warranty, express or implied, and all implied warranties of merchantability and fitness for a particular purpose are hereby disclaimed. Seller shall not be liable for prospective profits or special indirect or consequential damages. Seller's sole liability and buyer's exclusive remedy for breach of any warranty as expressly limited, at seller's option, to replacement at the original F.O.B. point or refund of purchase price. Seller shall not be responsible for any claim resulting from failure to utilize product in the manner in which it was intended and in accordance with instruction provided for use of product. Any claim for breach of warranty shall be deemed waived unless buyer shall give seller written notice of such claim within sixty (60) days after delivery and shall allow seller reasonable opportunity to investigate claim and inspect product.